

LANDSCAPE SOLUTIONS



Tree Spades

Dig, Lift and Transport Trees in Less Time.

In the late 1960's, Vermeer revolutionized the landscaping industry when it introduced "instant shade" to the market. Vermeer tree spades do it all — dig, lift and transport — in no time. Vermeer tree spades include features such as narrow, open-frame designs and short towers for improved maneuverability. Safety lockouts and transport locks increase safety. These features, and many more, make Vermeer tree spades the ideal choice for landscaping jobs or high-volume ball-and-burlap operations. Get the tree spade advantage for your business — buy Vermeer tree spades. Talk to your dealer today!

Tree spades from the industry pioneer and leader. Vermeer tree spades offer the best of all worlds: rugged performance and long-lasting value.



TS3300



A specialized tree spade with a special design. Vermeer specialty spades can be mounted to front end loaders for use by nurseries municipalities or contractors. These spades feature fast hydraulic cylinders with chain drive, replaceable wear bars that can be replaced in minutes and long-lasting industrial plastic slides in the spade towers.



TS44A

The industry's most popular choice for good reason. *Midsized spades feature bolt-on spades that make blade replacement easy, hydraulic tongue extensions to increase maneuverability and wide rear-gate openings to reduce tree damage.*

Model	TS20	TS30	TS3300	TS44A	TS44t	TS50m
Ball	20"	30"	33"	44"	44"	48" – 52"
Diameter	(51 cm)	(76 cm)	(84 cm)	(112 cm)	(112 cm)	(122 cm – 132 cm)
Ball	18"	26"	29"	40"	40"	48"
Depth	(46 cm)	(66 cm)	(74 cm)	(102 cm)	(102 cm)	(122 cm)
Tree Ball	109 lb	355 lb	600 lb	1173 lb	1173 lb	1900 lb
Weight	(49 kg)	(161 kg)	(272 kg)	(532 kg)	(532 kg)	(862 kg)
Mounting System	3-point	3-point	3-point/Skid steer	Trailer	Truck	Truck
Recommended Trunk Diameter	2" (5 cm)	3" (8 cm)	3" (8 cm)	4" (10 cm)	4" (10 cm)	5" (13 cm)

The mini-spade with extra-large productivity — mini-spades feature a heavy design that improves the spade's ability to penetrate the ground. Locking gates keep the machine stable when working in harder soil conditions.

TS20



Vermeer®

Vermeer Manufacturing Company
 1210 Vermeer Road East
 P.O. Box 200
 Pella, Iowa 50219 U.S.A.
 Phone: (641) 628-3141
 Fax: (641) 621-7734
 International fax: +1 (641) 621-7730
 www.vermeer.com

Call toll-free 1-888-VERMEER
 1-888-837-6337 (U.S.A. only)

Europe, Middle East and Africa:
 P.O. Box 323
 4460 AS Goes
 Netherlands
 Phone: +31 113 272700
 Fax: +31 113 272727



Equipment shown is for illustrative purposes only and may display optional accessories or components. Please contact your local Vermeer dealer for more information about machine specifications. Vermeer Manufacturing Company reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation.

VERMEER and VERMEER LOGO are registered trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. SHERRILL is a registered trademark of Sherrill Incorporated. © 2004 Vermeer Manufacturing Company. All Rights Reserved.